

THERE IS A REASON YOU INVESTED IN THE BEST.

KEEP IT PURE HINO



HINO TRUCKS GENUINE ENGINE OIL

- ENGINEERED & APPROVED BY HINO MOTORS LIMITED
- FOR USE IN ALL HINO TRUCKS | ALL MODEL YEARS





PUREHINO

ENGINEERED FOR ALL HINO TRUCKS

HINO GENUINE SYNTHETIC BLEND ENGINE OIL: achieves a new standard for today's high performance diesel engine oils. Its advanced protection technology breaks the mold for low temperature flow, extreme wear protection, breakdown resistance, reduced deposits & overall top shelf quality.

WEAR REQUIREMENTS: Hino Genuine Oil far exceeds the CK-4 wear requirements ensuring long term engine performance & reliability.

EMISSION SYSTEM COMPLIANCE: This special low ash formulation reduces the blocking of particulate filters and the poisoning of exhaust after-treatment devices, helping to maintain vehicle emission compliance.

FUEL ECONOMY: Independent test results have proven that Hino Genuine Oil provides notable fuel economy benefits when compared to other 15W-40 viscosity products.

EXTENDED OIL LIFE: Additionally, Hino Genuine Oil provides extended drain intervals (up to 20,000 miles), keeping your truck where it belongs - moving down the road.

HINO GENUINE MOTOR OIL MEETS THE FOLLOWING SPECIFICATIONS

SPECIFICATIONS & RECOMMENDATIONS

HINO GENUINE SYNTHETIC BLEND MOTOR OIL 10W-30 CK-4

TYPICAL PHYSICAL CHARACTERISTICS

SAE Grade: 10W-30 (CK-4, CJ-4, CI-4 Plus, CI-4, CH-4)
Viscosity @100°C, ASTM D445: 12.1 cSt
Viscosity @40°C, ASTM D445: 83 cSt
Viscosity Index: 142
Flash Point: 225°C
Pour Point: -39°C
Gravity: API 32.37
Pounds per Gallon: 7.190
Ash Content: 1.0% mass
Total Base Number ASTM D2896: 9.6 mg KOH/g

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Safety Data Sheet.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Improve your bottom line - **KEEP IT PUREHINO.**

ENGINES & EQUIPMENT

- Hino Trucks - All Model Years
- Cummins CES 20086, 81
- API CK-4, CJ-4, CI-Plus, CI-4, CH-4
- API SN
- ACEA E9
- Caterpillar ECF-3, ECF-2
- Cummins CES 20086, 81
- Detroit Fluids Specification (DFS) 93K222, 93K218
- Deutz DQC III-10 LA
- JASO DH-2
- Mack EOS-4.5, EO-O Premium Plus
- MAN M 3575
- MB-Approval 228.31
- MTU Category 2.1
- Volvo VDS-4.5, VDS-4

PART NUMBER DESCRIPTION

PART NUMBER	DESCRIPTION
15000-0008	1 gallon jug 3 gallon jugs per case 24 cases per pallet 72 total gallons per pallet
15000-0009	55 gallon drum - 4 drums per pallet



HINO.COM